



MATERIAL DATASHEET

(Revision 20-09-2023)

GENERAL PROPERTIES

Compound name:	NDS-225
Compound description:	PTFE + 25% carbon
Color:	Dark grey
Operating temperature range:	-190°C to +315°C
Approvals/certifications:	n/a

PHYSICAL PROPERTIES

Property	Specified	Test result	Unit	Standard
Hardness	-	63	Shore D	-
Specific gravity	2,20+/-0,02	2.10	g/cm ³	ASTM D 792
Tensile strength CD	≥ 14	-	N/mm ² (MPa)	ASTM D 638
Elongation at break CD	≥180	-	%	ASTM D 638
Deformation under load (140 Kg/cm ² per 24 hours at 23°C)	5.0-6.0	-	%	ASTM D 621
Permanent deformation (24 hours at 23°C)	1.8-2.2	-	%	ASTM D 621
Coefficient of linear thermal expansion (T=25-100°C)	7.0-12.0	-	10 ⁻⁵ /°C	ASTM D 696
Volume resistivity	10 ⁴	-	Ω * cm	ASTM D 257
Coefficient of dynamic friction	0.11	-	-	ASTM D 1894 – 78
Wear coefficient (PV=100 (kg*m)/(cm ³ /min))	30-40	-	(cm ³ *min)/ (kg*m*h)*10 ⁻⁸	

*In normal conditions: +23°C/50% relative humidity
CD: Cross Direction*

Disclaimer

This information is to the best of our knowledge accurate to the date indicated. However, NewDealSeals make no warranty, expressed or implied that parts manufactured from this material will perform satisfactorily in the customer's application. It is the customer's responsibility to evaluate parts prior to use, especially in applications where their failure may result in injury and/or damage. It should also be noted that all elastomeric parts have a finite life, therefore a regular program of inspection and replacement is strongly recommended. TGA, infrared and other types of analysis must be agreed, fixed and approved by both parties with specifications and tolerances; on the contrary results can neither confirmed nor guaranteed. Nothing herein shall be construed as a recommendation to infringe any existing patent or violate any applicable law. The distribution of this document is not monitored. This data sheet is not subject to an automatic update.